



## TOP COAT DRIVEWAY SEALER AND FILLER TECHNICAL DATA & INSTRUCTIONS

---

### DESCRIPTION

**TOP COAT DRIVEWAY SEALER AND FILLER** is a heavy duty, aggregate reinforced sealer used to seal asphaltic pavement.

---

### FEATURES

- Heavy duty aggregate - reinforced emulsion aids in filling in cracks
- Helps provide an anti-skid surface on steep grades; helps eliminate slippery conditions
- Covers 75-100 square feet per gallon, depending on roughness of the asphalt and whether the surface has been previously coated.

---

### HOW TO USE

Fill all cracks with **CRACK GONE** and holes with **REPAIR**. Clean surface of dirt, oil, gasoline and foreign material. Surface can be damp, but no free standing water. Apply **TOP COAT DRIVEWAY SEALER AND FILLER** when the temperature is above 50°F and is not expected to freeze within 24 hours. Heavy rain before material dries will wash sealer away. Apply early in the morning using either a rubber-edged squeegee or a bristle brush. Do not apply too thick, or **TOP COAT DRIVEWAY SEALER AND FILLER** will be unable to cure properly. If a thicker application is desired, apply a second coat after 24 hours cure time. Allow 24 hours after each coat before parking cars or driving on fresh sealer. Assure **TOP COAT DRIVEWAY SEALER AND FILLER** is thoroughly mixed before using and after each pour-out.

---

### SPECIFICATIONS

**Physical Form:** Viscous Liquid

**Color:** Black

**Odor:** Slight Petroleum

**Specific Gravity:** > 1.00

**Flash Point (TCC):** None



For more information on EpoxyMaster products please visit:

[www.epoxymaster.com](http://www.epoxymaster.com)

EpoxyMaster · 900 Wilshire Drive, Suite 202 · Troy, MI 48084-4726 · (888) 376-9954

© 2015 EpoxyMaster